## NSN 5930-00-051-0813

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-051-0813

### **Thread Class:**

2a single threaded stud

### Thread Length:

0.250 inches single threaded stud

## **Overall Length:**

5.407 inches

#### **Overall Height:**

1.288 inches

#### **Overall Width:**

1.531 inches

**Body Length:** 

2.000 inches

#### **Operating Tempurature Rating:**

70.0 degrees celsius and -65.0 degrees celsius

#### **Mounting Method:**

Threaded stud

## Features Provided:

Electrical access port

### **Contact Action Stimulus:**

Increase

## Thread Size:

0.190 inches single threaded stud

### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

## **Terminal Type:**

Tab, solder lug

### **Contact Load Current Rating:**

5.0 amperes resistive load first voltage

### Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

85.00 actuation point feet per minute and 700.00 deactuation point feet per minute and 85.00 differential point feet per minute

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

### Media For Which Designed:

Gas or liquid

#### Style Designator:

Rectangular

## Thread Series Designator:

Unf single threaded stud

### Shelf Life:

N/a

# NSN 5930-00-051-0813

Flow Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

