

View Online at <https://aerobasegroup.com/nsn/5930-00-052-3129>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.438 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.406 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0