## NSN 5930-00-052-3138

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-052-3138

External deactuation point screw and external actuation point screw

view Online at https://aerobasegroup.com/nsn/5930-00-052-3136
Inside Diameter:
0.250 inches single connection
Overall Length:
5.812 inches
Overall Height:
4.750 inches
Overall Width:
2.375 inches
Body Length:
4.750 inches
Body Height:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Differential
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
160.00 pounds per square inch gage
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+5.00 to 75.00 actuation point pounds per square inch gage and +5.00/+75.00 deactuation point pounds per square inch gage
Contact Adjustment Type:

## NSN 5930-00-052-3138

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: ---

**Demilitarization:** 

No Fiig: A048b0