

View Online at <https://aerobasegroup.com/nsn/5930-00-052-6006>

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.500 inches

Overall Height:

Between 1.781 inches and 2.093 inches

Overall Width:

Between 1.531 inches and 2.031 inches

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.843 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 4th section front

Throw Quantity:

4 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 4th section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Specification Data:

81349-mil-s-3786/1c government specification

Specification Or Standard:

Sr01n30a1hgo style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0