

View Online at <https://aerobasegroup.com/nsn/5930-00-052-6589>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

Between 0.735 inches and 0.765 inches

**Bushing Length:**

0.625 inches

**Body Length:**

Between 0.719 inches and 0.781 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

Between 0.800 inches and 0.860 inches

**Actuator Free Position Height:**

Between 0.800 inches and 0.860 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

32.0 ounces

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

0.008 differential inches and 0.040 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

6.000 amperes resistive dc and 2.500 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0