

View Online at <https://aerobasegroup.com/nsn/5930-00-052-6589>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

Between 0.735 inches and 0.765 inches

Bushing Length:

0.625 inches

Body Length:

Between 0.719 inches and 0.781 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

Between 0.800 inches and 0.860 inches

Actuator Free Position Height:

Between 0.800 inches and 0.860 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

32.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

0.008 differential inches and 0.040 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 2.500 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0