NSN 5930-00-053-3746

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-053-3746

Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.766 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.900 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.406 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
Actuator Roller Width: 0.150 inches
0.150 inches
0.150 inches Maximum Voltage Rating In Volts:
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type:
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method:
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
0.150 inches Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:
Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch unit
Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch unit Switch Release Force:

Between 0.188 pretravel inches and 0.312 pretravel inches and 0.140 overtravel inches and 0.012 differential inches and 0.062 differential

inches

Actuator Movement:

NSN 5930-00-053-3746

Sensitive Switch - Page 2 of 2



Contact	Load Cu	rrent Ratin	a At Maxin	num Rated	Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0