

View Online at <https://aerobasegroup.com/nsn/5930-00-054-0192>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

1.315 inches

Overall Height:

0.480 inches

Overall Width:

0.480 inches

Body Diameter:

0.480 inches

Bushing Length:

0.280 inches

Actuator Style:

Round

Actuator Height:

0.330 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.705 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 500.000 milliamperes inductive dc and 500.000 milliamperes lamp dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac and 500.000 milliamperes lamp ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNF

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms18152 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0