

View Online at <https://aerobasegroup.com/nsn/5930-00-054-0369>

**Overall Length:**

2.094 inches

**Overall Height:**

2.625 inches

**Overall Width:**

0.938 inches

**Distance Between Mounting Facility Centers:**

0.688 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Capillary tube end seal connection and manual reset button

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches all threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

1.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+100.00 to 450.00 actuation point pounds per square inch and +100.00/+450.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

250.00 actuation point pounds per square inch and 200.00 deactuation point pounds per square inch and 50.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0