## NSN 5930-00-054-4458

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-054-4458

n	nerating	<b>Tempurature</b>	Rating:
_	berailliu	remburature	naumu.

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:** 

Threaded bushing and line

**Features Provided:** 

Hermetically sealed case

Thready Qty Per Inch (tpi):

14 single threaded bushing

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Wire lead

**Contact Load Current Rating:** 

500.0 milliamperes resistive load second voltage

**Contact Adjustability:** 

Actuation point not adjustable

**Contact Stimulus Rating:** 

30.50 actuation point gallons per minute

**Contact Voltage Rating In Volts:** 

32.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

**Thread Series Designator:** 

Npt single threaded bushing

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A048b0