## NSN 5930-00-054-6463

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-054-6463

Body Style:
Hole mounted
Overall Length:
4.437 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.531 inches
Overall Height:
1.188 inches
Overall Width:
0.875 inches
Bushing Length:
0.422 inches
Body Width:
0.875 inches
Body Height:
1.188 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Actuator Style:
Round
Actuator Height:
0.984 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position locked in and center position no locking action
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
120.0 ac
Inclosure Type:
Uninclosed
Mounting Method:
Threaded hole
Thready Qty Per Inch (tpi):
32
Pile-up Contact Form Arrangement:
2c 2nd position
Thread Size:
0.469 inches
Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

## **NSN 5930-00-054-6463** Lever Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contacts palladium
Thread Series Designator:
Uns
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0