# NSN 5930-00-055-3354

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-055-3354

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.000 inches

#### **Overall Height:**

1.500 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.875 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 9:00 o'clock

#### Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 single section rear

#### **Throw Quantity:**

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

## Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-055-3354

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.5 amperes resistive load dc at sea level

#### Precious Material And Location:

Contact surfaces silver

**Precious Material:** 

Silver

# Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0