

View Online at <https://aerobasegroup.com/nsn/5930-00-055-5027>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Diameter:

0.023 inches

Actuator Height:

0.010 inches

Actuator Free Position Height:

0.320 inches

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Special Features:

Included are 1 retaining spring, 2 plates, 1 actuator, 2 mtg screws

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0