# NSN 5930-00-056-2448

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-056-2448

## Thread Class:

2a single mounting facility

## Thread Length:

0.438 inches single mounting facility

## Hazardous Locations/environmental Protection:

Explosion proof

#### **Overall Length:**

2.924 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.214 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.438 inches single actuator

## **Overall Diameter:**

1.125 inches

## Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

4

#### Nonturn Device Type:

Tab at 3: 00 o'clock

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

10 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Shaft Flat/slot Angular Location:

216.0 degrees from nonturn device single actuator

## **Rotor Through Connection Quantity:**

1 each section

## NSN 5930-00-056-2448

Rotary Switch - Page 2 of 2



## Switch Actuator Indexing Position Quantity:

10 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

1.0 amperes inductive load dc at sea level

## Style Designator:

Tap, circular, bushing mount

## Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator: Unef single mounting facility Specification Data: 96906-ms16109 government standard Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0