# NSN 5930-00-056-4960

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-056-4960

# **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Height:**

1.625 inches

## First Flat Length:

0.343 inches single actuator

#### Flat Height:

0.218 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.469 inches single actuator

## Individual Section Quantity:

1

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

6 each section front

# Throw Quantity:

2 each section rear

## Mounting Method:

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

24.0 dc at sea level

## **Rotor Through Connection Quantity:**

6 each section

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Switch Actuator Stop Device Type:

Adjustable stop single actuator

# NSN 5930-00-056-4960

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

200.0 milliamperes resistive load ac at sea level

#### **Precious Material And Location:**

Terminals and contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0