NSN 5930-00-056-7626

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-056-7626 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 3.150 inches **Overall Height:** Between 0.796 inches and 0.828 inches **Overall Width:** Between 0.796 inches and 0.828 inches **Body Diameter:** Between 0.796 inches and 0.828 inches **Bushing Length:** 0.625 inches **Body Length:** Between 0.796 inches and 0.828 inches **Maximum Voltage Rating In Volts:** 200.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac **Thread Series Designator:** Unef **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-056-7626

Push Switch - Page 2 of 2



Fiig:

A053a0