

View Online at <https://aerobasegroup.com/nsn/5930-00-056-7626>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

3.150 inches

**Overall Height:**

Between 0.796 inches and 0.828 inches

**Overall Width:**

Between 0.796 inches and 0.828 inches

**Body Diameter:**

Between 0.796 inches and 0.828 inches

**Bushing Length:**

0.625 inches

**Body Length:**

Between 0.796 inches and 0.828 inches

**Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0