NSN 5930-00-056-7791

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-056-7791

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Weatherproof |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Overall Height: |
| 1.486 inches |
| Overall Width: |
| 0.687 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 1.040 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Style: |
| Roller plunger |
| Actuator Free Position Height: |
| 1.235 inches |
| Actuator Roller Diameter: |
| 0.235 inches |
| Actuator Roller Width: |
| 0.250 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |

4.0 ounces

Switch Release Force:

NSN 5930-00-056-7791 Sensitive Switch - Page 2 of 2



| Switch Actuating Force: |
|--|
| 12.0 ounces |
| Actuator Movement: |
| Between 0.015 pretravel inches and 0.100 overtravel inches and 0.001 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive ac |
| Precious Material And Location: |
| Contacts silver |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |