# NSN 5930-00-057-5845

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-057-5845

## **Overall Length:**

0.880 inches

## **Overall Height:**

0.413 inches

## **Overall Width:**

0.776 inches

## Body Length:

0.436 inches

#### **Body Width:**

0.776 inches

## **Body Height:**

0.250 inches

## Unthreaded Mounting Hole Diameter:

#### 0.125 inches

## **Distance Between Mounting Facility Centers:**

0.625 inches

## Tempurature Sensing Element Type:

Internal sensor

## **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 205.0 degrees fahrenheit

## Mounting Method:

Bracket and unthreaded hole

## **Contact Action Stimulus:**

Decrease

## Mounting Facility Pattern:

Two position in-line

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

## **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

2.3 amperes resistive load first voltage

## Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

## **Contact Adjustment Range:**

-20.00/+200.00 actuation point degrees fahrenheit and -20.00 to 200.00 deactuation point degrees fahrenheit

## Contact Adjustment Type:

External deactuation point screw and external actuation point screw

## **Contact Stimulus Rating:**

185.00 actuation point degrees fahrenheit and 190.00 deactuation point degrees fahrenheit

## Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

## NSN 5930-00-057-5845

Thermostatic Switch - Page 2 of 2

Frequency In Hertz:

400.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

