

View Online at <https://aerobasegroup.com/nsn/5930-00-058-7786>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.780 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.750 inches

Actuator Style:

Leaf

Actuator Width:

0.160 inches

Actuator Free Position Height:

0.350 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.218 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0