NSN 5930-00-058-7786

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-058-7786

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.780 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.750 inches
Actuator Style:
Leaf
Actuator Width:
0.160 inches
Actuator Free Position Height:
0.350 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.218 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac
Terminal Type And Quantity:
3 solder stud
Shelf Life:

N/a

NSN 5930-00-058-7786

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0