NSN 5930-00-059-2734

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-059-2734

Thread Class:

2a single mounting facility

Overall Length:

2.875 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.938 inches single actuator

Distance Between Mounting Facility Centers:

1.500 inches single mounting facility

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-059-2734

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0