NSN 5930-00-059-3594

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-059-3594

Thread Class:

2a single mounting facility

Thread Length:

0.368 inches single mounting facility and 0.385 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.777 inches

Shaft Diameter:

0.500 inches single actuator

Shaft Length:

0.275 inches single actuator

Overall Diameter:

Between 0.490 inches and 0.510 inches

Individual Section Quantity:

1

Operating Tempurature Range:

-55.0 to 125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.216 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.25 milliamperes resistive load dc at sea level

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

NSN 5930-00-059-3594

Rotary Switch - Page 2 of 2

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

