NSN 5930-00-059-4323



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-059-4323 **Body Style:** Hole mounted Center To Center Distance Between Mounting Facilities Parallel To Length: 0.500 inches **Body Length:** 0.781 inches **Body Width:** 0.250 inches **Body Height:** 0.437 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.140 inches **Switch Actuator Quantity: Actuator Free Position Height:** 0.840 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 2.0 ounces **Switch Actuating Force:** 5.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.120 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-00-059-4323 Sensitive Switch - Page 2 of 2



Fiig:

A053a0