

View Online at <https://aerobasegroup.com/nsn/5930-00-059-4323>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.437 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.140 inches

**Switch Actuator Quantity:**

1

**Actuator Free Position Height:**

0.840 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.120 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0