## NSN 5930-00-059-4323

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-059-4323

#### **Body Style:**

Hole mounted

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

#### **Body Length:**

0.781 inches

#### **Body Width:**

0.250 inches

### Body Height:

0.437 inches

#### **Case Material:**

Plastic

#### **Unthreaded Mounting Hole Diameter:**

#### 0.188 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.140 inches

Switch Actuator Quantity:

1

#### **Actuator Free Position Height:**

0.840 inches

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

#### Switch Release Force:

2.0 ounces

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

Between 0.050 pretravel inches and 0.120 overtravel inches and 0.020 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

#### **Terminal Type And Quantity:**

2 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 5930-00-059-4323** Sensitive Switch - Page 2 of 2

Fiig: A053a0

