

View Online at <https://aerobasegroup.com/nsn/5930-00-060-4694>

Thread Class:

2a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

8.940 inches

Outside Diameter:

0.312 inches single connection

Body Length:

2.200 inches

Overall Diameter:

1.375 inches

Pressure Switch Type:

Gage

Mounting Method:

Line

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch gage

Thread Size:

0.312 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

14.50 actuation point pounds per square inch gage and 12.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0