NSN 5930-00-060-9739

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-060-9739

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.218 inches
Overall Height:
1.302 inches
Overall Width:
1.312 inches
Body Length:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.205 inches
Operating Tempurature Rating:
130.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
1550.00 actuation point feet per minute and 1460.00 actuation point feet per minute and 1500.00 actuation point feet per minute and
1280.00 actuation point feet per minute and 1450.00 deactuation point feet per minute and 1335.00 deactuation point feet per minute and
1375.00 deactuation point feet per minute and 1115.00 deactuation point feet per minute and 50.00 differential point feet per minute and
115.00 differential point feet per minute and 125.00 differential point feet per minute and 165.00 differential point feet per minute
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:

Vec - demil/mli

Demilitarization:

NSN 5930-00-060-9739 Flow Switch - Page 2 of 2



Fiig:

A048b0