

View Online at <https://aerobasegroup.com/nsn/5930-00-062-3704>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof and shock proof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.356 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Length:**

0.630 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.562 inches

**Actuator Roller Diameter:**

0.187 inches

**Actuator Roller Width:**

0.150 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.219 pretravel inches and 0.030 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0