

View Online at <https://aerobasegroup.com/nsn/5930-00-062-6964>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Width Between Flats:

0.214 inches single actuator and 0.217 inches single actuator

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.480 inches

Shaft Diameter:

0.310 inches single actuator

Shaft Length:

0.400 inches single actuator

Overall Diameter:

2.640 inches

Nonturn Device Radius:

0.430 inches at 8: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 8: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

12.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

25.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0