

View Online at <https://aerobasegroup.com/nsn/5930-00-063-9118>

Thread Class:

2a single threaded bushing

Thread Length:

0.437 inches single threaded bushing

Overall Length:

2.781 inches

Body Diameter:

0.250 inches

Body Length:

1.375 inches

Bulb Length:

33.750 inches

Bulb Diameter:

Between 0.136 inches and 0.158 inches

Temperature Sensing Element Type:

Bulb

Width Across Flats:

0.625 inches

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.375 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-50.00 to 300.00 actuation point degrees fahrenheit and -49.00 to 299.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

300.00 actuation point degrees fahrenheit and 299.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

32.0 dc at sea level second voltage

Special Features:

2.000 in. Lg wire leads

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0