## NSN 5930-00-063-9118

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-063-9118

**Thread Class:** 2a single threaded bushing **Thread Length:** 0.437 inches single threaded bushing **Overall Length:** 2.781 inches **Body Diameter:** 0.250 inches **Body Length:** 1.375 inches **Bulb Length:** 33.750 inches **Bulb Diameter:** Between 0.136 inches and 0.158 inches **Tempurature Sensing Element Type:** Bulb Width Across Flats: 0.625 inches **Operating Tempurature Rating:** Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 24 single threaded bushing **Contact Action Stimulus:** Increase **Thread Size:** 0.375 inches single threaded bushing **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Wire lead **Contact Load Current Rating:** 1.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point adjustable, preset and actuation point adjustable, preset **Contact Adjustment Range:** -50.00 to 300.00 actuation point degrees fahrenheit and -49.00 to 299.00 deactuation point degrees fahrenheit **Contact Adjustment Type:** Internal deactuation point screw and internal actuation point screw

## Contact Stimulus Rating:

300.00 actuation point degrees fahrenheit and 299.00 deactuation point degrees fahrenheit

## NSN 5930-00-063-9118

Thermostatic Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 32.0 dc at sea level second voltage Special Features: 2.000 in. Lg wire leads Media For Which Designed: Liquid Style Designator: Cylindrical Thread Series Designator: Unf single threaded bushing Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0