

View Online at <https://aerobasegroup.com/nsn/5930-00-064-0737>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.825 inches

Overall Height:

1.156 inches

Overall Width:

0.688 inches

Body Length:

1.094 inches

Body Width:

0.625 inches

Body Height:

0.400 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.094 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.375 inches

Actuator Length:

0.156 inches

Actuator Style:

Rectangular

Actuator Height:

0.094 inches

Actuator Width:

0.094 inches

Actuator Free Position Height:

0.594 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

0.046 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Mtg on a metal bracket 2.531 in. Lg by 0.750 in. W; bracket contains tw0 0.250 in. Diameter mtg holes 2.000 in. C to c

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0