NSN 5930-00-064-0854

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-064-0854

Body Style:		
Hole mounted		
Hazardous Locations/environmental Protection:		
Dustproof		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
1.000 inches		
Body Length:		
3.040 inches		
Body Width:		
1.000 inches		
Body Height:		
1.750 inches		
Case Material:		
Metal		
Unthreaded Mounting Hole Diameter:		
0.138 inches		
Actuator Style:		
Round		
Actuator Diameter:		
0.330 inches		
Actuator Height:		
0.970 inches		
Actuator Free Position Height:		
2.720 inches		
Maximum Voltage Rating In Volts:		
120.0 ac and 125.0 dc		
End Application:		
Truck, fire/crash p2, truck, fire/crash p15.		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Unthreaded hole		
Nonpile-up Contact Arrangement:		
1 pole, double throw, one position momentary single switch unit		
Switch Release Force:		
11.0 ounces		
Criticality Code Justification:		
Feat		
Switch Actuating Force:		
Retween 9.0 ounces and 24.0 ounces		

Actuator Movement:

0.002 differential inches and 0.078 pretravel inches

NSN 5930-00-064-0854

Sensitive Switch - Page 2 of 2



Contact Load Current Ratio	g At Maximum	Rated Voltage:
----------------------------	--------------	----------------

0.500 amperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0