NSN 5930-00-064-0854

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-064-0854

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

3.040 inches

Body Width:

1.000 inches

Body Height:

1.750 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.138 inches

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

0.970 inches

Actuator Free Position Height:

2.720 inches

Maximum Voltage Rating In Volts:

120.0 ac and 125.0 dc

End Application:

Truck, fire/crash p2, truck, fire/crash p15.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

11.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 9.0 ounces and 24.0 ounces

Actuator Movement:

0.002 differential inches and 0.078 pretravel inches

NSN 5930-00-064-0854

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0