

View Online at <https://aerobasegroup.com/nsn/5930-00-064-2904>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

3.124 inches

**First Flat Length:**

0.250 inches 2nd actuator

**Flat Height:**

0.216 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.812 inches 2nd actuator

**Overall Diameter:**

2.188 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

270.0 degrees from nonturn device all actuators

**Switch Actuator Indexing Position Quantity:**

8 all actuators

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees all actuators

**Detent Rotational Torque Range:**

+28.000/+96.000 inch-ounces all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0