

View Online at <https://aerobasegroup.com/nsn/5930-00-064-6859>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

Between 1.620 inches and 1.640 inches

Overall Height:

Between 1.300 inches and 1.320 inches

Overall Width:

Between 1.240 inches and 1.260 inches

First Flat Length:

0.430 inches single actuator and 0.450 inches single actuator

Flat Height:

0.180 inches single actuator and 0.200 inches single actuator

Shaft Diameter:

0.240 inches single actuator and 0.260 inches single actuator

Shaft Length:

0.870 inches single actuator and 0.890 inches single actuator

Nonturn Device Radius:

0.520 inches at 3:00 o'clock and 0.540 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

400.0 milliamperes inductive load dc at sea level

Special Features:

Switch in position no. 3 spring return from other positions to center. There shall be detent feel at positions 2, 3, and 4

Style Designator:

Circular wafer, bushing mount

Test Data Document:

06481-900027-56 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0