

View Online at <https://aerobasegroup.com/nsn/5930-00-064-6859>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.370 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:**

Between 1.620 inches and 1.640 inches

**Overall Height:**

Between 1.300 inches and 1.320 inches

**Overall Width:**

Between 1.240 inches and 1.260 inches

**First Flat Length:**

0.430 inches single actuator and 0.450 inches single actuator

**Flat Height:**

0.180 inches single actuator and 0.200 inches single actuator

**Shaft Diameter:**

0.240 inches single actuator and 0.260 inches single actuator

**Shaft Length:**

0.870 inches single actuator and 0.890 inches single actuator

**Nonturn Device Radius:**

0.520 inches at 3: 00 o'clock and 0.540 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

400.0 milliamperes inductive load dc at sea level

**Special Features:**

Switch in position no. 3 spring return from other positions to center. There shall be detent feel at positions 2, 3, and 4

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

06481-900027-56 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0