

View Online at <https://aerobasegroup.com/nsn/5930-00-064-7399>

**Body Style:**

Hole mounted

**Overall Length:**

0.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.365 inches and 0.373 inches

**Overall Width:**

0.250 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.345 inches and 0.366 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.077 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.087 inches and 0.097 inches

**Actuator Free Position Height:**

Between 0.315 inches and 0.345 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

Between 3.0 ounces and 5.0 ounces

**Actuator Movement:**

Between 0.025 pretravel inches and 0.035 pretravel inches and 0.008 overtravel inches and 0.0025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0