

View Online at <https://aerobasegroup.com/nsn/5930-00-064-7683>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and oiltight and waterproof

Overall Length:

5.000 inches

Overall Height:

2.438 inches

Overall Width:

3.000 inches

Case Material:

Metal

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.625 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

1.938 inches

Housing Length:

5.000 inches

Housing Width:

2.281 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.750 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Switch Release Force:

45.0 inch-ounces

Switch Actuating Force:

190.0 inch-ounces

Actuator Movement:

17.0 pretravel degrees and 80.0 overtravel degrees and 11.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 12.000 amperes resistive ac

Special Features:

1-0, 2-nc, ccw operation to 1-c, 2-0, cw spring return to 1-n0, 2-nc

Terminal Type And Quantity:

9 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0