

View Online at <https://aerobasegroup.com/nsn/5930-00-064-8134>

Thread Class:

2a single mounting facility

Thread Length:

0.360 inches single mounting facility and 0.400 inches single mounting facility

Overall Length:

Between 2.145 inches and 2.215 inches

Overall Height:

Between 1.860 inches and 1.900 inches

Overall Width:

Between 1.570 inches and 1.610 inches

First Flat Length:

0.290 inches single actuator and 0.330 inches single actuator

Flat Height:

0.213 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.745 inches single actuator and 0.755 inches single actuator

Nonturn Device Radius:

0.526 inches at 9:00 o'clock and 0.536 inches at 9:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-25.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 3rd section rear

Throw Quantity:

4 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

230.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

15 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Special Features:

1 dummy lug sect. 1, rear

Style Designator:

Circular wafer, bushing mount

Test Data Document:

80063-smc423294 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0