

View Online at <https://aerobasegroup.com/nsn/5930-00-064-9134>

Body Style:

Bushing mount

Overall Length:

Between 1.105 inches and 1.135 inches

Overall Height:

2.740 inches

Overall Width:

Between 0.605 inches and 0.635 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 1.105 inches and 1.135 inches

Body Width:

Between 0.605 inches and 0.635 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.110 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Actuator Position-locking Relationship:

Down position locked out

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Mounting Surface To Terminal End Distance:

Between 1.145 inches and 1.175 inches

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 6.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0