

View Online at <https://aerobasegroup.com/nsn/5930-00-065-0453>

Width Between Flats:

0.184 inches single actuator

Overall Length:

2.407 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

First Flat Length:

0.812 inches single actuator

Shaft Diameter:

0.251 inches single actuator

Shaft Length:

0.938 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.687 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.594 inches single mounting facility

Operating Temperature Range:

-40.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

8 single section rear

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+2.000 to 6.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0