

View Online at <https://aerobasegroup.com/nsn/5930-00-065-1932>

Thread Class:

2a single mounting facility

Thread Length:

14.98 millimeters single mounting facility

Overall Length:

72.37 millimeters

Overall Diameter:

52.57 millimeters

Nonturn Device Radius:

16.56 millimeters at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.625 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 highest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

40.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

35.0 amperes resistive load lowest dc voltage rating at sea level and 25.0 amperes inductive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0