NSN 5930-00-065-5697

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

2 single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-065-5697

Dustproof
Overall Length:
2.844 inches
Overall Height:
2.500 inches
Overall Width:
2.406 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.375 inches single actuator
Unthreaded Mounting Hole Diameter:
0.203 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
2.094 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
2 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:

NSN 5930-00-065-5697 Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0