# NSN 5930-00-065-6173

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-065-6173

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Height:**

1.437 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.250 inches single actuator

### Nonturn Device Radius:

0.438 inches at 9:00 o'clock

### Individual Section Quantity:

1

### Knob Manufacturer Code:

71590

# Knob Manufacturer Part Number:

P-120

### Nonturn Device Type:

Tab at 9: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section rear

#### **Throw Quantity:**

11 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

# **Features Provided:**

Actuator knob

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

6.0 lowest dc voltage rating at sea level

# Switch Actuator Indexing Position Quantity:

11 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Makes before breaks single section rear

# NSN 5930-00-065-6173

Rotary Switch - Page 2 of 2



**Switch Actuator Positioning Increment:** 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 5.5 amperes resistive load highest dc voltage rating at sea level **Special Features:** Index assembly, rotary **Precious Material And Location:** Terminal surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0