

View Online at <https://aerobasegroup.com/nsn/5930-00-065-8595>

**Inside Diameter:**

0.438 inches single connection

**Thread Length:**

0.500 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.906 inches

**Overall Height:**

2.094 inches

**Overall Width:**

4.812 inches

**Body Length:**

2.531 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.937 inches

**Longest Vertical Distance Between Mounting Centers:**

2.156 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

2500.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+50.00/+1000.00 actuation point pounds per square inch and +50.00/+1000.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point hex nut and internal actuation point hex nut

**Contact Stimulus Rating:**

15.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0