

View Online at <https://aerobasegroup.com/nsn/5930-00-065-8595>

Inside Diameter:

0.438 inches single connection

Thread Length:

0.500 inches single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.906 inches

Overall Height:

2.094 inches

Overall Width:

4.812 inches

Body Length:

2.531 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.937 inches

Longest Vertical Distance Between Mounting Centers:

2.156 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+1000.00 actuation point pounds per square inch and +50.00/+1000.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Stimulus Rating:

15.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0