

View Online at <https://aerobasegroup.com/nsn/5930-00-065-8977>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.375 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.625 inches

Overall Height:

2.500 inches

Overall Width:

2.125 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.531 inches single actuator

Individual Section Quantity:

9

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

12 each section rear

Mounting Facility Circle Radius:

0.718 inches 2nd mounting facility

Mounting Method:

Threaded hole 2nd mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

125.0 milliamperes inductive load ac at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0