

View Online at <https://aerobasegroup.com/nsn/5930-00-065-8978>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.375 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

4.594 inches

**Overall Height:**

2.500 inches

**Overall Width:**

2.500 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.531 inches single actuator

**Individual Section Quantity:**

6

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

12 each section rear

**Mounting Facility Circle Radius:**

0.718 inches 2nd mounting facility

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Metallic inclosure

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Mounting Facility Pattern:**

Three position circular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes inductive load ac at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0